

P86SH118-Txx

HIGH TORQUE IP65 Bipolar Stepping motor - 1,8°



Introduction

The P86SH118-Txx is a bipolar stepper motor with terminal-box, with IP65 protection optionally equipped with a Push-Pull or Line-Driver incremental encoder. The connection of the motor is made through a 7/8" circular connector, and the connection of the encoder is made through a M12 circular connector.




IP65



Specifications


Model	Current/phase	Resistance/phase	Inductance/phase	Detent torque	Holding torque	Rotor inertia	Encoder	Weight
P86SH118-T-C	6 A	0,45 Ω	5.1 mH	230 mNm	8,7 Nm	2700 gcm ²	-	3,8 Kg
P86SH118-TO0512P24C	6 A	0,45 Ω	5.1 mH	230 mNm	8,7 Nm	2700 gcm ²	Push-pull	3,8 Kg
P86SH118-TO0512L05C	6 A	0,45 Ω	5.1 mH	230 mNm	8,7 Nm	2700 gcm ²	Line-driver	3,8 Kg

Mechanical dimensions



IP65 motor housing, except output flange

Speed vs Torque curve



The torque curves are made with AEP torque transducer mod. MRT250NM

Motor characteristics

Step Angle	1,8° ± 5%
Insulation Class	B
Protection degree	IP65 (except output flange)
Ambient Temperature	-20 °C .. +50 °C
Temperature Rise	80°C max (2 phase ON)
Insulation Resistance	100 M Ω min 500Vdc
Dielectric Strength	820 V _{AC} FOR ONE MINUTE
Shaft Radial Play	0,02mm (with 450g load)
Shaft Axial Play	0,08mm (with 450g load)
Max Radial Force	220N (20mm FROM FRONT FLANGE)
Max Axial Force	60 N max

Caution

Insert and tighten firmly the connectors before powering the motor. **Never disconnect any connector when powered.** Installation and maintenance must be carried out by qualified technicians only. The operator must have detailed information to be able to carry out this work.


- Unexpected dangers may be encountered
- An incorrect use may destroy this product and the connected equipments.

P86SH118-Txx

HIGH TORQUE IP65 Bipolar Stepping motor - 1,8°



Connectors layout




Encoder characteristics

	PUSH-PULL	LINE DRIVER
V _{SUPPLY}	+24 V _{DC}	+5 V _{DC}
I _{MAX} (NO LOAD)	80 mA	
I _{MAX}	60 mA each channel	
F _{OUT} MAX	300 KHz	
COUNT/REV	512	
PROTECTION DEGREE	IP54	
WORKING TEMPERATURE	-20 .. +80 °C	

Motor connector

M1

7/8 5 Pin male




PIN	Description	Cable color matching	
1	Phase A	BLACK	
2	Phase A -	BLUE	
3	GND	YELLOW/GREEN	
4	Phase B	BROWN	
5	Phase B -	WHITE	

Push-Pull encoder connector

M2

M12 5 Pin female




PIN	Description	Cable color matching	
1	V _{IN} (+24V _{DC})	BROWN	
2	Channel A	WHITE	
3	Common	BLUE	
4	Channel B	BLACK	
5	Channel Z	GREY	

Line-Driver encoder connector

M2

M12 8 Pin male



PIN	Description	Cable color matching	
1	Channel Z +	WHITE	
2	V _{IN} (+5V _{DC})	BROWN	
3	Channel A +	GREEN	
4	Channel A -	YELLOW	
5	Channel B +	GREY	
6	Channel B -	PINK	
7	Common	BLUE	
8	Channel Z -	RED	

Ordering code

